



Similar to illustration

### Toploader **BT 300/13**

⊕	Volume	<b>300 litres</b>
⊙	Int. dimensions (w x d x h)	<b>920 x 570 x 610 mm</b>
⊞	Power	<b>15 kW</b>

## Technical data

### ☰ Overview

Product group	<b>Kiln</b>
Design	<b>Toploader</b>
Type	<b>BT series</b>

### ⏻ Energy

Energy type	<b>Electrical</b>
Power	<b>15 kW</b>
Supply	<b>25 A</b>
Voltage	<b>3/N/PE 400V AC</b>
Connection	<b>CEE 32 A</b>

### ⊕ Dimensions

Volume	<b>300 litres</b>
Int. dimensions (w x d x h)	<b>920 x 570 x 610 mm</b>
Ext. dimensions (W x D x H)	<b>1360 x 970 x 1070 mm</b>
Weight	<b>400 kg</b>

### ☆ Equipment

Insulation	<b>2-layer</b>
Heating	<b>5-side</b>
Heating elements	<b>Recessed into bricks</b>
Control	<b>TC 504</b>

**Besondere Merkmale****Torsion-resistant welded steel housing**

The housing consists of a torsion-resistant welded construction. Each furnace is manufactured by hand and leaves the factory after undergoing extensive quality controls.

**Durable textured paint finish**


The high-quality light-grey RAL 7035 textured coating protects the furnace body and steel construction.

**Safe lid opening thanks to the robust lid**


The lid comprises a robust lid hinge and a gas pressure spring allows for easy lid opening.

**Air supply handle**

The manual air supply handle ensures the best possible ventilation of the furnace interior.

**Exhaust air flap handle**

The manual exhaust air flap handle is available for the controlled removal of gases and hot exhaust air.

**Efficient 2-layer insulation structure**

A sophisticated 2-layer insulation structure allows for required temperatures to be achieved using less energy. High energy efficiency can be achieved even in continuous use.

**First-class useful volume**

All insulating materials are processed precisely and carefully. Lightweight firebricks in the firing chamber are characterised by a high insulation value and good thermal shock resistance.

**Covered heating elements on the floor**

A high-quality SiC plate protects heating elements mounted on the floor. The SiC plate guarantees good heat transfer and at the same time protects the heating elements from damage.

### Easy-to-maintain switchgear mounted in a connection box

The switchgear is mounted in a stainless steel connection box and can be easily maintained and accessed.




### Integrated safety due to door contact switch

A door contact switch automatically isolates the heating elements from the power supply when the kiln opens. The integrated overtemperature protection prevents damage to electrical components.

### Low-wear contactors for control

The furnace is controlled by low-wear, durable contactors.




### 5-side heating allows for good heat distribution

Heating from 5 sides (side walls, back wall, door and floor) results in very good heat distribution throughout the firing chamber.

### Durable heating elements made of “Kanthal A1”

We are committed to minimal surface load and precise manufacture when dimensioning “Kanthal A1” heating elements, so a long service life is guaranteed.




### Heating elements securely recessed into bricks

Heating elements are recessed in protected position into bricks and achieve high energy input and provide ideal protection against mechanical damage.

### Heating elements can be easily accessed and serviced

An easy-to-access detachable cover for heating element connections allows the effortless replacement of heating elements.



### Precise temperature measurement with the “Type S” thermocouple

The installed PtRhPt thermocouple (type S) is protected against damage and guarantees exact temperature measurement at all times.



**The “CEE 32 A” connector allows for easy connection**

The standardised CEE 32 A connector allows for easy connection and quick and safe start-up.

**Components from well-known manufacturers contribute to long service life**

We only obtain our electric components from well-known manufacturers (e.g. SIEMENS, MOELLER, WEIDMÜLLER, RITTAL).

**Furnace construction in accordance with DIN EN 746-1**

The unit is constructed and manufactured in accordance with DIN EN 746-1 Industrial Thermoprocessing Equipment.

**Switchgear design in accordance with DIN EN 60519**

The switchgear is designed in accordance with DIN EN 60519 Safety in Installations for Electroheating.

**2-year warranty despite intense use**

We deliberately refuse to reduce the warranty period despite commercial furnaces being used intensely except parts that are subject to wear.