



Similar to illustration

Toploader TE 10 Q

⊕	Volume	10 litres
⊙	Int. dimensions (w x d x h)	180 x 230 x 230 mm
⏻	Power	1.8 kW
Ⓒ	Tanw *	1290°C

* **Application temperature** for long-term and continuous use.

Technical data

☰ Overview

Product group	Kiln
Design	Toploader
Type	TE-Q series

⏻ Energy

Energy type	Electrical
Power	1.8 kW
Supply	8 A
Voltage	1/N/PE 230V AC
Connection	Schuko connector


⊕ Dimensions

Volume	10 litres
Int. dimensions (w x d x h)	180 x 230 x 230 mm
Ext. dimensions (W x D x H)	390 x 600 x 560 mm
Weight	30 kg

☆ Equipment

Insulation	2-layer
Heating	4-side
Heating elements	Recessed into bricks
Control	ST 310

Besondere Merkmale



Long-term application temperature Tapp 1290°C

The kiln is designed for long-term and continuous use at temperatures up to 1290°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firing as well as high-temperature stoneware, soft paste porcelain firings. These applications correspond to Seger Cone 8 or Orton Cone 9.



Power supply with 230 V "Schuko" plug connector

The high-quality insulation allows the kiln to be fired safely at stoneware temperatures using a regular 230 V "Schuko" plug connector (3.6 kW).



Gas pressure spring-supported opening mechanism for the lid

The sturdy lid construction is supported by gas pressure springs that allow easy, effortless and safe opening of the lid.



High-quality heating elements

With the heating elements made from "Kanthal A1" we attach great importance to a low surface load and a careful production. The heating elements are reliable and durable thanks to a sufficient reserve capacity in the calculation.



3-year warranty

We produce each kiln by hand and keep to strict quality guidelines. Therefore, we offer a voluntary 36-months warranty to extend legal warranty regulations.