



Similar to illustration

Toploader TE 35 Q

⊕	Volume	35 litres
⊙	Int. dimensions (w x d x h)	380 x 380 x 230 mm
⏻	Power	3.6 kW
Ⓒ	Tanw *	1290°C

* **Application temperature** for long-term and continuous use.

Technical data

☰ Overview

Product group	Kiln
Design	Toploader
Type	TE-Q series

⏻ Energy

Energy type	Electrical
Power	3.6 kW
Supply	16 A
Voltage	1/N/PE 230V AC
Connection	Schuko connector


⊕ Dimensions

Volume	35 litres
Int. dimensions (w x d x h)	380 x 380 x 230 mm
Ext. dimensions (W x D x H)	630 x 780 x 570 mm
Weight	81 kg

☆ Equipment

Insulation	2-layer
Heating	4-side
Heating elements	Recessed into bricks
Control	ST 310

Besondere Merkmale



Long-term application temperature Tapp 1290°C

The kiln is designed for long-term and continuous use at temperatures up to 1290°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firing as well as high-temperature stoneware, soft paste porcelain firings. These applications correspond to Seger Cone 8 or Orton Cone 9.



Power supply with 230 V "Schuko" plug connector

The high-quality insulation allows the kiln to be fired safely at stoneware temperatures using a regular 230 V "Schuko" plug connector (3.6 kW).



Gas pressure spring-supported opening mechanism for the lid

The sturdy lid construction is supported by gas pressure springs that allow easy, effortless and safe opening of the lid.



3-year warranty

We produce each kiln by hand and keep to strict quality guidelines. Therefore, we offer a voluntary 36-months warranty to extend legal warranty regulations.