



Similar to illustration

## Toploader **TG 220**

|   |                             |                           |
|---|-----------------------------|---------------------------|
| ⊕ | Volume                      | <b>220 litres</b>         |
| ⊙ | Int. dimensions (w x d x h) | <b>650 x 640 x 690 mm</b> |
| ⏻ | Power                       | <b>40 kW</b>              |
| Ⓒ | Tanw *                      | <b>1320°C</b>             |

\* **Application temperature** for long-term and continuous use.

## Technical data

### ☰ Overview

|               |                  |
|---------------|------------------|
| Product group | <b>Kiln</b>      |
| Design        | <b>Toploader</b> |
| Type          | <b>TG series</b> |

### ⏻ Energy

|             |                  |
|-------------|------------------|
| Energy type | <b>Gas-fired</b> |
| Power       | <b>40 kW</b>     |
| Burners     | <b>2 pieces</b>  |

### ⊕ Dimensions

|                             |                            |
|-----------------------------|----------------------------|
| Volume                      | <b>220 litres</b>          |
| Int. dimensions (w x d x h) | <b>650 x 640 x 690 mm</b>  |
| Ext. dimensions (W x D x H) | <b>1020 x 930 x 990 mm</b> |
| Weight                      | <b>180 kg</b>              |

### ★ Equipment

|            |                              |
|------------|------------------------------|
| Insulation | <b>2-layer</b>               |
| Heating    | <b>Propangas Topfbrenner</b> |

## Besondere Merkmale



### Long-term application temperature Tapp 1320°C

The kiln is designed for long-term and continuous use at temperatures up to 1320°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firing as well as high-temperature stoneware, soft paste porcelain firings. These applications correspond to Seger Cone 10 or Orton Cone 11.