



Similar to illustration

## Toploader TE 130 MCC+ DH

|   |                             |                      |
|---|-----------------------------|----------------------|
| ⊕ | Volume                      | <b>130 litres</b>    |
| ⊙ | Int. dimensions (w x d x h) | <b>Ø590 x 460 mm</b> |
| ⏻ | Power                       | <b>8.8 kW</b>        |
| Ⓒ | Tanw *                      | <b>1240°C</b>        |

\* **Application temperature** for long-term and continuous use.

## Technical data

### ☰ Overview

|               |                          |
|---------------|--------------------------|
| Product group | <b>Kiln</b>              |
| Design        | <b>Toploader</b>         |
| Type          | <b>TE-MCC+ DH series</b> |

### ⏻ Energy

|             |                       |
|-------------|-----------------------|
| Energy type | <b>Electrical</b>     |
| Power       | <b>8.8 kW</b>         |
| Supply      | <b>16 A</b>           |
| Voltage     | <b>3/N/PE 400V AC</b> |
| Connection  | <b>CEE 16 A</b>       |

### ⊕ Dimensions

|                             |                                                    |
|-----------------------------|----------------------------------------------------|
| Volume                      | <b>130 litres</b>                                  |
| Int. dimensions (w x d x h) | <b>Ø590 x 460 mm</b>                               |
| Ext. dimensions (W x D x H) | <b>870 x 940 x 820 mm),<br/>870 x 940 x 820 mm</b> |
| Weight                      | <b>106 kg</b>                                      |

### ☆ Equipment

|                  |                             |
|------------------|-----------------------------|
| Insulation       | <b>2-layer</b>              |
| Heating          | <b>All-around</b>           |
| Heating elements | <b>Recessed into bricks</b> |
| Control          | <b>ST 411</b>               |